LAMP_® UNIT SHELF (TYPE B) XL-US02B **INSTALLATION MANUAL B** Thank you for selecting our product. Before starting installation, please read this manual thoroughly to ensure correct installation. Please keep this manual at hand for future reference. Meaning of symbols Warning Prohibited Required Caution Load Capacity (N) 294 N / shelf Load Capacity (Kgf) 30 Kgf / shelf **Glass thickness** 8 or 10 mm for 8 mm glass Max. 1200 mm Glass width for 10 mm glass Max. 1500 mm Glass depth 400 mm - 450 mm Height of vertical frame 2000 - 2500 mm **Component Parts (for four glass shelves)** Leveling leg: 4 pcs Vertical Frame : 2 pcs (Length 2500 mm) 40 Fixing screw 8x75 : 4 pcs Clamp XL-USO1-F20: 8 pcs Œ (with Hexagon socket set screw M4x6) 0 Hexagon socket head bolt M5x14:8 pcs Fixing ϕ 16 : 4 pcs Clamp XL-USO1-B20: 8 pcs R (with Hexagon socket set screw M4x6) Bracket (L): 2 pcs Square nut : 16 pcs 0 Hexagon socket countersunk head screw M6x20:8 pcs Bracket (R): 2 pcs Rod: 2 pcs Rod fitting (top) (φ6x1415 mm) (φ20x55 mm) : 2 pcs Hexagon socket set screw

Square nut: 16 pcs





M4x8 : 2 pcs

M4x4 : 4 pcs


Hexagon socket set screw

Rod fitting (bottom)


(φ20x55 mm) : 2 pcs

(q25x48 mm) : 2 pcs

Rod fitting cover (bottom)









Assembling Rod


- (1) Screw rod fitting (top) into the fitting on bracket until it stops.
- (2) Screw rod fitting (bottom) into the fitting on lower bracket temporarily.
- (3) Assemble rod fitting cover (bottom) on rod fitting (bottom).
- (4) Insert set screw M4x4 into rod fitting (top) and rod .fitting (bottom)



- on the rod temporarily. (2) Clamp Fix XL-USO1-B20
- (3) Make sure that four clamps are fixed in the same height.

(4) Fix the clamps firmly.

æ



(4).

Hexagon socket set screw M4x4

Clamp XL-USO1-F20 (for rod) (1)Hexagon socket head bolt M5x14 æ Tool: Hex key 3 mm (3) Set screw (4) (with plastic tip)

Tool: Hex key 2 mm

▲ Caution ·

Handle glass plates with care.

Insert glass plate from the front. Check the position of glass plate, then tighten set screws firmly.

Fitting

SUGATSUNE KOGYO CO.,LTD. Tokyo, JAPAN Phone: +81 (0)3 3866 2260 E-mail: export@sugatsune.co.jp

SUGATSUNE KOGYO (UK) LTD. Reading,UK Phone: +44 118 9272 955 E-mail: sales@sugatsune.co.uk

SUGATSUNE EUROPE GmbH Düsseldorf, GERMANY Phone: +49,211 53812900 E-mail: info@sugatsune.eu

SUGATSUNE KOGYO INDIA PRIVATE LIMITED Mumbai, INDIA Phone: +91 22 28314490/91 E-mail: sales@sugatsune.in

SUGATSUNE SHANGHAI Co., LTD. Shanghai, CHINA Phone: +86 21 3632 1858 E-mail: lamp@sugatsune.com.cn

Guangzhou, CHINA Phone: +86 20 6639 3552 E-mail: lamp@sugatsune.com.cn SUGATSUNE AMERICA, INC. California, USA Phone: +1 310 329 6373 E-mail: sales@sugatsune.com

Chicago, USA Phone: +1 312 461 1081 E-mail: chicagoshowroom@sugatsune.com 2017.01 0190-3

ISO9001(Japan Offices and Sugatsune America) and ISO14001(Chiba Production division and Logistics center), certified.