# LAMP. UNIT SHELF (TYPE K) XLA-US02K INSTALLATION MANUAL

Thank you for selecting our product. Before starting installation, please read this manual thoroughly to ensure correct installation. Please keep this manual at hand for future reference.

Meaning of symbols




Prohibited



Required

Load Capacity (N)	490 N / shelf
Load Capacity (Kgf)	50 Kgf / shelf
Glass thickness	10 mm
Glass width	Max. 1092 mm
Glass depth	Max. 450 mm
Height of vertical frame	Max. 2500 mm



#### **Component Parts (for four glass shelves)**



Leveling leg: 4 pcs




Fixing screw 8x75: 4 pcs



Fixing φ16: 4 pcs



Point fixing bracket: 6 pcs





Shelf support: 6 pcs



Point fix PE32: 12 pcs (φ32x30mm)




Hexagon socket head cap screw M8x12: 12 pcs



Washer φ16: 12 pcs



# 2 Cutting Vertical Frame



L = Installation height - 100 mm (Floor - Ceiling mounting)

L = Vertical frame length - 100 mm (Wall mounting)

✓ !\ Caution

Wear protective eyewear when cutting.

#### ·<u>∕</u> Caution -

Cut the frames at right angle. It may result in warp of shelving if the cutting is not correct.

3 Assembly of Vertical Frame

- (1) Couple Leveling leg with vertical frame.
- (2) Fix Leveling leg with fixing screw.

Fix Leveling leg on another end, too.

### 4. Mount of fixing φ16

Wall mount

Mount fixing only on the floor.

Floor - Ceiling mounting Mount fixing on the floor and the ceiling.


Fixing screws (not provided)

Recommended screws For wooden surface

: use 4x6 20 mm or bigger tapping screws.

For concrete surface

: use 4x6 20 mm or bigger plastic anchors.



Philips screwdriver


Fixing screw 8x75

Leveling leg

Vertical frame





# 5 Position of Glass Shelf



Measurement between two vertical frames (center to center): Max. 1200 mm

6 Installing Vertical Frame






∕!∖Caution -

Do not assemble glass shelves until vertical frames are fixed.


For floor - ceiling mounting, cover fixing  $\phi$ 16 by loosing Leveling leg. Use  $\phi$ 2.5 bar or hex key to turn the adjusting part when it gets tight.


7 Preparation of Glass Shelves







Prepare 3 glass plates.









#### Assembling point fixing




#### Mount of point fixing

Loosen the screws on the shelf support, then clamping parts are closed and ready to be assembled. Tighten the screw to fasten the shelf support after assembling.







Tool: Hex key 4 mm Make sure that the clamping parts on the shelf support are fastened to both vertical frame and point fixing bracket firmly.

# Assembling glass plates

**∕!**∖Caution -

Handle glass plates with care.

Tool: Pin spanner wrench Z058 (sold separately) Cap of point fixing PE32



SUGATSUNE KOGYO (UK) LTD

Reading, UK
Phone: +44 118 9272 955 E-mail:sales@sugatsune.co.uk

E-mail:lamp@sugatsune.com.cn

E-mail:lamp@sugatsune.com.cn

Chicago, USA

SUGATSUNE AMERICA, INC

SUGATSUNE EUROPE GmbH Düsseldorf, GERMANY Phone: +49 211 53812900 E-mail:sales@sugatsune.eu

SUGATSUNE KOGYO INDIA PRIVATE LIMITED Mumbai, INDIA
Phone: +91 22 28314490/91 E-mail:sales@sugatsune.in

California, USA
Phone: +1 310 329 6373 E-mail:sales@sugatsune.com

Phone: +1 312 461 1081 E-mail:chicagoshowroom@sugatsune.com.

Guangzhou, CHINA

Phone: +86 20 6639 3552